

# SCAFFOLD FITTINGS & ACCESSORIES

## Single Couplers

A rapid fitting for the erection of putlogs and transoms to a permanent fixture.

### ◆ Drop Forged Plated



### ◆ Pressed Steel Plated



## Double Couplers

### ◆ Drop Forged Plated (available in Black)



### ◆ Pressed Steel Plated



Double couplers provide a self-gripping/wrapping facility which provides a strong positive grip when connecting standards to ledgers.

Conform to BS1139 Part 2 1982

## Swivel Couplers


### ◆ Pressed Steel



### ◆ Drop Forged Plated (Also available in Black and Galv.)

Swivel couplers provide a tough positive grip enabling two tubes to be connected together at any angle, especially for use in cross bracing. Conform to BS1139 Part 2 1982

## Scaffold Tube



Available in:

- ◆ Galv
- ◆ Alloy
- ◆ Black

Range of Putlogs available



Tube End Protectors also available.

## Castors



A selection of various types and design of Castor Wheels to suit all demands. All castors are designed to swivel and are fitted with a simple but effective brake.

## Adjustable Fork Head




Designed to support joints. Heads can be installed in to either a prop or scaffold tube. This unit provides up to 150mm of adjustment.


## Stage Bracket

This unit enables the working platform to be extended inside the scaffold up to the fascia.

Available in either 2 or 3 board width.



## Brickguards



A strong mesh construction that simply clips to ledger tubes, providing personnel protection from falling objects.

## SCAFFOLD FITTINGS &amp; ACCESSORIES



## Debris Netting &amp; Sheeting

A wide range of debris netting and sheeting to meet all applications. A full range of builders tarpaulins are also available. All of the above are available in Flame Retardant upon request.

## Rope



A wide and comprehensive selection of ropes to meet all scaffold/hoist requirements. Polypropylene, Sisal etc. BSI Rated rope available.

## Rubbish Chutes



Range consists of Top Hopper, Chutes c/w chains, Side Entry Systems and winches.

## Scaffold Tagging Systems



Range of Scaffold tagging systems. Full range of inserts available, including customised for specific needs.

## Scaffold Belts &amp; Frogs



## Harness's &amp; Fall Arrest



Scaffolders full body harness complete with integral lanyard and large karabiner. Part of the comprehensive range of fall arrest harness's and accessories stocked.

Full range of fall arrester's available.



## Loading Bay Gates



Full range of gates from leading manufacturers for conventional and system scaffolding.

## Pole Ladders



Full range of pole ladders for all applications. From reinforced timber to non-spark epoxy coated ladders.

## Staging



450mm and 600mm staging. 600mm staging complies with new safety legislation. Full hand rail system available.



### Fixed Finial Coupler

For a secure 90° handrail connection.  
Weight: 0.81kg Code: 003601

### Putlog Coupler - Standard

For connection of putlogs and transoms to standard scaffold tube whilst allowing scaffold boards to be laid on top of the tube.  
Weight: 0.67kg Code: 006300



### Prop Bracing Double Coupler

Provides a 90° positive fixing enabling the connection of standard scaffold tube, prop outers or any tube.  
Weight: 0.91kg Code: 423200



### Prop Bracing Swivel Coupler

Provides a strong positive diagonal bracing connection of standard tube and prop outers or any 60mm O/D tube at any angle.  
Weight: 1.03kg Code: 423201



### Swivel Finial Coupler

For a tough handrail securement whilst providing a 15-90° adjustment of the railing.  
Weight: 0.72kg  
Code: 003602



### Single Coupler

Enables scaffold tube to be connected to a permanent fixture. Available pierced or unpierced.  
Pierced Weight: 0.46kg Code: 010730  
Unpierced Weight: 0.47kg Code: 010729



### Supa Tie® (1)

Designed to secure any scaffold tube or transom at right angles to the face of a masonry wall. Unique cam action allows for non-accurate alignment.  
Weight: 1.09kg Code: 009002  
Finish: body - sheradised  
anchor bolt - galvanised.

### Supa Tie® E Type(2)

Designed to secure scaffold tubes running parallel to a masonry wall at any angle.  
Weight: 1.23kg Code: 009001  
Finish: body - sheradised  
anchor bolt - galvanised.  
M16 Wall Anchor is also available.



### Technical Information

Supa Tie® and Supa Tie® E Type  
The tensile strength depends almost totally on the condition of the fabric of the building in which the anchor sleeve is installed.

Calibrated pull out tests by trained personnel are recommended.

### Joist Coupler

A unique way of securing scaffold tubes to timber joists.



To Fit Joist	Weight:	Code:
50mm	1.40kg	558607
75mm	1.40kg	152024
100mm	1.51kg	558608

### Lattice Brace Coupler

For quick conversion of standard scaffold tube into load bearing columns and beams with 305mm centres.

Weight: 1.60kg Code: 006800  
Finish: zinc coated and chrome passivated.



### Stair Tread Bracket

Designed with integral swivel coupling for quick fixing of stair treads which can be adjusted from 28° to 90°.

Weight: 1.44kg Code: 006600  
Finish: zinc coated and chrome passivated.



### Stair Tread Complete

A fully assembled 914mm stair tread. Special widths are available to order.  
Weight: 6.87kg Code: 008900



### 3 Guard Board Clip

Provides secure connection of guard boards to standard scaffold tube.  
Based on 38mm board.

Weight: 0.12kg  
Code: 008400



## SCAFFOLD FITTINGS

# KDK Scaffolding Ltd

## Sleeve Coupler

A one piece heavy duty coupler for rapid connection featuring a central baffle plate for correct tube positioning and unique individual one side unhooking safety feature.

Weight: 1.13kg Code: 006000  
Conforms to BS1139 Part 2 1982. Safe working loads to BS5973.  
Tension load: 3kN



## Roofing Coupler

Designed for 'hole-free' rapid clamping of scaffold tube above and below corrugated sheeting.

Weight: 1.41kg Code: 017600



## Roofing Coupler

The galvanised steel or plastic coated sheet has a corrugation pitch of 76.2mm and thickness of 0.5mm to 0.7mm.

## Joint Pin

Designed for internal 'end-to-end' connection of standard scaffold tube


Weight: 0.85kg Code: 006400  
Conforms to BS1139 Part 2 1982.



## Double Coupler

A self-gripping/wrapping facility which provides a strong positive grip when connecting standards to ledgers.

Weight: 0.91kg Code: 006100  
Maximum safe working loads to BS5973.  
Slip along tube: 6.3kN  
Conforms to BS1139 Part 2 1982.



## Putlog Coupler - Mk3

For rapid erection or dismantling of putlogs and transoms. Featuring a special one piece "wrap-over".


Weight: 0.77kg Code: 006700  
Maximum safe working loads to BS5973.  
Slip along tube: 0.53kN  
Conforms to BS1139 Part 2 1982.



## Fencing Coupler

A strong, high quality coupler designed to secure metal fencing panel uprights together

Weight: 0.65kg  
Code: 611500



## Swivel Coupler

A tough positive grip enabling two tubes to be connected together at any angle, especially for use in cross bracing.

Weight: 1.02kg Code: 006200  
Maximum safe working loads to BS5973.  
Slip along tube: 6.3kN  
Conforms to BS1139 Part 2 1982.

## Gravlock® Girder Couplers

For fast secure coupling of tube to 'T' beam flanges up to 45mm thick whilst comfortably exceeding the BS1139 slip requirements.

NB must always be used in pairs.

Weight: 1.47kg  
Codes: Self colour 007800; shearsided 007800;  
ZCCP 152015  
Maximum safe working loads to BS5973.  
Slip of coupler along section 10kN  
Slip of tube through coupler 6.5kN  
Hanging load vertically 30kN

All loads are based on PAIRS of Gravlock uniformly and concentrically loaded.



## Putlog Head

Quickly converts a standard scaffold tube into a putlog, enabling maximum utilisation of scaffold tube stocks.

Weight: 0.54kg  
Code: 004600






**Fitting End Cap**




**Tube End Cap**



**Gin Wheel**



**Tredda Plate**




**Wire Lashing**




**Scaffold Sign Board Frame.** Galvanised, sizes 20" x 30" or 24" x 36"



**Sole Board**



**Board and Batten Band, Plates and Nails**



**Ladder Access Safety Gate**



**Fitting Bin**



**Stillages - 4 post**